


Manufacturing date	Q1/2020
ATEX marking EESF 20 ATEX 014X	 II 2 GD Ex eb IIC T4/T3 Gb Ex tb IIIC T70°C Db
IECEX marking IECEX EESF 20.0003X	Ex eb IIC T4/T3 Gb
Product description	Explosion protected portable or transportable transformer
Temperature classification	T3 or T4
Operating temperature	-20°C ... +55°C
Supply Voltage (min-max)	110V, 230V +/- 6%
Supply Current typical	2A or 4A
Output voltage	12VAC, 24VAC or 42VAC
Output current	Max. 16A
Number of outputs	Low voltage: 2 or 4 (ATEX and IECEX) Low voltage: 3 + 1 mains for linking (ATEX only)
Electrical class	Class I
Maximum load	42VAC 384W 24VAC 384W 12VAC 192W
Cable	H07BQ-F or H-Flex
Plug and socket options	ATX, CEAG (IECEX only with CEAG)
Enclosure	Aluminium case, stainless steel frame
Ingress protection	IP66
Weight (without cable and plug)	ATEX & IECEX 19kg (incl. 4x sockets)
Warranty	You will find detailed warranty conditions from http://www.atexor.com/downloads/

	Dimensions / mm		
	L	W	H
SLAM® TrafoEX	585	295	310

